Version 1.1

"Developed from the UNFCCC CDM conception".



April 2020



Version I.I – Scope I7

I. INTRODUCTION

This tool provides a step-by-step method for estimating carbon stocks and change in carbon stocks in dead wood and/or waste in the baseline and project scenarios of a ZERO2NATURE-PREFOR project activity. The tool provides methods based on field measurements. Simplified methods based on conservative default factors are also available where certain conditions are met.

2. SCOPE, APPLICABILITY, AND ENTRY INTO FORCE

2.1. Scope

This tool can be used for estimation of carbon stocks and change in carbon stocks in dead wood and/or waste in the baseline and project scenarios of A ZERO2NATURE-PREFOR project activity.

2.2. Applicability

This tool has no internal applicability conditions.

This tool makes the following assumptions:

(a) Linearity of change of biomass in dead wood and waste over a period of time:

Change of biomass in dead wood and waste may be assumed to proceed, on average, at an approximately constant rate between two points of time at which the biomass is estimated;

(b) Appropriateness of root-shoot ratios:

Root-shoot ratios appropriate for estimation of below-ground biomass from above-ground biomass of living trees are also appropriate for dead trees.

2.3. Entry into force

The date of entry into force of this Tool's updated version is May 4, 2020.

3. NORMATIVE REFERENCES

The following documents are indispensable for the application of this tool:

(a) Glossary of ZERO2NATURE terms;



Version I.I – Scope 17

(b) Tool "Estimation of carbon stocks and change in carbon stocks of trees and shrubs in ZERO2NATURE-PREFOR project activities";

(c) ZERO2NATURE standard.

4. DEFINITIONS

The definitions contained in the Glossary of ZERO2NATURE terms shall apply. Where a term is not defined in the Glossary of ZERO2NATURE terms, project participants should consult the definitions provided in the *IPCC Good Practice Guidance for Land Use, Land-Use Change and Forestry* (IPCC GPG-LULUCF 2003).

5. PARAMETERS

This tool provides procedures to determine the following parameters:

Table 1. Parameters determined by the tool

Parameter	Unit	Description	
C _{DW,y}	tEIP	Carbon stock in dead wood within the project boundary at a given point of time in year y	
$\Delta C_{DW,y}$	tEIP	Change in carbon stock in dead wood within the project boundary in year y	
$C_{LI,y}$	tEIP	Carbon stock in wastewithin the project boundary at a given point of time in year y	
ΔC _{LI,y} tEIP Change in carbon stock in waste within the project boundary in year y		Change in carbon stock in wastewithin the project boundary in year y	

While applying this tool in a methodology, the following notation should be used:

(a) In the baseline scenario:

 $C_{DW_BSL,y}$ for $C_{DW,y}$ and $C_{W_BSL,y}$ for $C_{W,y}$;

 $\Delta C_{DW_BSL,y}$ for $\Delta C_{DW,y}$ and $\Delta C_{W_BSL,y}$ for $\Delta C_{W,y}$.

(b) In the project scenario:

 $C_{DW_PROJ,y}$ for $C_{DW,y}$ and $C_{W_PROJ,y}$ for $C_{W,y}$;

 $\Delta C_{DW_{PROJ,y}}$ for $\Delta C_{DW,y}$ and $\Delta C_{W_{PROJ,y}}$ for $\Delta C_{W,y}$



Version I.I – Scope 17

6. ESTIMATION OF CARBON STOCK AND CHANGE IN CARBON STOCK IN DEAD WOOD

Carbon stock in dead wood is estimated on the basis of the same strata, and the same sample plots, which are used for the purpose of estimation of living tree biomass. However, project participants (PPs) applying this tool may use a different stratification for the purpose of estimation of carbon stock in dead wood if transparent and verifiable information can be given for justification of such a choice.

Two methods are offered for estimation of carbon stock in dead wood: a measurement-based method and a conservative default-factor based method.

6.1. Measurement-based methods for estimation of carbon stock in dead wood

For the purpose of this tool, the term "species" also implies a group of species when a biometric parameter (e.g. biomass expansion factor, root-shoot ratio, basic wood density) or a model (e.g. allometric equation, volume equation or table) is applicable to more than one species.

Biomass of dead wood of species j in sample plot p in stratum i at a given point of time in year y is calculated separately for the following two types of dead wood:

- (a) Standing dead wood;
- (b) Lying dead wood.

Note: Uprooted trees lying on the ground, if not extracted, shall be treated as "standing dead wood" for estimation of deadwood biomass.

6.1.1. Standing dead wood

For the following two categories of standing dead wood, the biomass of standing dead wood is estimated by applying a biomass reduction factor to whole tree biomass:

(a) Dead trees which have lost only leaves and twigs.

Dead wood biomass is equal to whole tree biomass multiplied by a biomass reduction factor equal to 0.975;

(b) Dead trees which have lost leaves, twigs and small branches (diameter ≤ 10 cm).

Dead wood biomass is equal to whole tree biomass multiplied by a biomass reduction factor equal to 0.80.



Version I.I – Scope 17

6.1.1.1. Estimation of standing dead tree biomass using BEF method

Under this method volume tables (or volume functions/curves) are used to convert tree dimensions to stem volume of trees. Stem volume of trees is converted to above-ground tree biomass using basic wood density and biomass expansion factors and the above-ground tree biomass is expanded to total tree biomass using root-shoot ratios. Thus, dead wood biomass in standing dead trees of species *j* in sample plot *p* is calculated as:

$$B_{DWS_TREE,j,p,i,y} = D_j \times BEF_{2,j} \times (1+R_j) \times \sum_{k=1}^{K} V_{TREE,j} (DBH_k, H_k) \times \alpha_k$$
 Equation (1)

Where:			
B _{DWS_TREE,j,p,i,y}	=	Biomass of dead wood in dead trees of species <i>j</i> in sample plot <i>p</i> of stratum <i>i</i> at a point of time in year <i>y</i> ; t d.m.	
$V_{TREE,j}(DBH_k,H_k)$	=	Stem volume of the k^{th} dead tree of species <i>j</i> in plot <i>p</i> of stratum <i>i</i> as returned by the volume function for species <i>j</i> using the tree dimension(s) as entry data; m ³	
DBH _k	=	Diameter of the k^{th} dead tree of species <i>j</i> in plot <i>p</i> of stratum <i>i</i> at a point of time in year <i>y</i> ; metre or any other unit of length used by the volume function	
H_k	=	Height of the k^{th} dead tree of species <i>j</i> in plot <i>p</i> of stratum <i>i</i> at a point of time in year <i>y</i> ; metre or any other unit of length used by the volume function	
α_k	=	Biomass reduction factor for the <i>k</i> th dead tree, depending upon its category; dimensionless	
Dj	=	Basic wood density of species <i>j</i> ; t d.m. m ⁻³	
$BEF_{2,j}$	=	Biomass expansion factor for conversion of stem biomass to above-ground tree biomass, for species <i>j</i> ; dimensionless	
R _j	=	Root-shoot ratio for tree species <i>j</i> ; dimensionless	
j	=	1, 2, 3, tree species in plot p	
k	=	1, 2, 3, dead trees of species <i>j</i> in plot <i>p</i> in stratum <i>i</i>	
p	=	1, 2, 3, sample plots in stratum i	
i	=	1, 2, 3, biomass estimation strata within the project boundary	
У	=	<i>1, 2, 3,</i> years elapsed since the start of the zero2NATURE-PREFOR project activity	



Version I.I – Scope 17

6.1.1.2. Estimation of standing dead tree biomass using allometric method

Under this method allometric equations are used to convert tree dimensions to above-ground biomass of trees and the above-ground tree biomass is expanded to total tree biomass using root-shoot ratios. Thus, dead wood biomass in standing dead trees of species *j* in sample plot *p* is calculated as:

$$B_{DWS_TREE,j,p,i,y} = (1+R_j) \times \sum_{k=1}^{K} f_j (DBH_k, H_k) \times \alpha_k$$
 Equation (2)

Where:

$B_{DWS_TREE, j, p, i, y}$	 Biomass of dead wood in standing dead trees of species j in sample plot p of stratum i at a point of time in year y; t d.m.
$f_j(DBH_k,H_k)$	Above-ground biomass of the k th dead tree of species j in sample plot p of stratum i returned by the allometric function for species j using the tree dimension(s) as entry data; t d.m.
α_k	 Biomass reduction factor for the kth dead tree, depending upon its condition; dimensionless
R _j	 Root-shoot ratio for tree species j; dimensionless
j	= 1, 2, 3, tree species in plot p
k	= 1, 2, 3, dead trees of species <i>j</i> in plot <i>p</i> in stratum <i>i</i>
p	= 1, 2, 3, sample plots in stratum i
i	= 1, 2, 3, biomass estimation strata within the project boundary
у	= 1, 2, 3, years elapsed since the start of the ZERO2NATURE-PREFOR project activity



Version I.I – Scope 17

6.1.1.3. Estimation of carbon stock in standing dead wood in dead trees

In both the *BEF* method and the allometric method, the carbon stock in dead wood biomass in standing dead trees of species *j* in sample plot *p* of stratum *i* is calculated as follows:

$$C_{DWS_TREE,j,p,i,y} = \frac{44}{12} \times CF_{TREE} \times B_{DWS_TREE,j,p,i,y}$$
Equation (3)

Where:

C _{DWS_TREE} , j, p, i, y	 Carbon stock in dead wood in standing dead trees of species j in sample plot p in stratum i at a given point of time in year y; t CO₂e
CFTREE	 Carbon fraction of tree biomass; dimensionless
$B_{DWS_TREE,j,p,i,y}$	Biomass of dead wood in standing dead trees of species j in sample plot p of stratum i at a point of time in yeary; t d.m.
j	= 1, 2, 3, tree species in plot p
p	= 1, 2, 3, sample plots in stratum i
i	= 1, 2, 3, biomass estimation strata within the project boundary
y .	= 1, 2, 3, years elapsed since the start of the ZERO2NATURE-PREFOR project activity

6.1.1.4. Estimation of carbon stock in standing dead wood in tree stumps

Each dead tree stump in a sample plot is categorized into a decay class as:

- (a) Sound;
- (b) Intermediate or
- (c) Rotten.

A density reduction factor is assigned to each of the decay classes, which is to be multiplied by the basic wood density of the species of the stump to obtain its estimated wood density. The following default values of the density reduction factors for the three decay classes are used, unless PPs have more specific data available with them: for the decay class:

- (a) Sound, the density reduction factor = 1.00, for the decay class;
- (b) Intermediate, the density reduction factor = 0.80, for the decay class and
- (c) Rotten, the density reduction factor = 0.45.



Version I.I – Scope I7

For each dead tree stump of height less than 4m the mid-height diameter is measured. For each dead tree stump of height 4m and above, the diameter at breast height (DBH) is measured.

Equation (4)

For stumps of height more than 4 m, the mid-height diameter of the stump is estimated as:

$$D_{MID_STUMP} = 0.57 \times DBH \times \left(\frac{H_{STUMP}}{H_{STUMP} - H_{DBH}}\right)^{0.80}$$
 for $H_{STUMP} > 4$ m

Where:

D _{MID_STUMP}	=	Mid-height diameter of the dead tree stump; m
DBH	=	Diameter at breast height of the dead tree stump; m
H _{STUMP}	=	Height of the stump; m
H _{DBH}	=	Height above ground level at which DBH is measured; m

Carbon stock in dead wood in dead tree stumps of species *j* in plot *p* is calculated as:

$C_{DWS_STUMP,j,p,i,y} = \frac{44}{12} \times CF_{TREE} \times D_j \times (1+R_j) \times \frac{\pi}{4} \sum_k D_{MID_STUMP,k}^2 \times D_k $	Equation (5)
$H_k * \beta_k$	

Where:

C _{DWS_STUMP} , j, p, i, y	 Carbon stock in dead wood in dead tree stumps of species j in sample plot p in stratum i at a given point of time in year y; t EIP
CF _{TREE}	 Carbon fraction of tree biomass; dimensionless
D_j	 Basic wood density of species j; t d.m. m⁻³
R _j	= Root-shoot ratio for tree species <i>j</i> ; dimensionless
D _{MID_STUMP,k}	 Mid-height diameter of the kth dead tree stump of species j in plot p in stratum i at a given point of time in year y; m
H_k	 Height of the kth dead tree stump of species j in plot p in stratum i at a given point of time in yeary; m
β_k	 Density reduction factor applicable to the kth dead tree stump of species <i>j</i> in plot <i>p</i> in stratum <i>i</i> at a given point of time in year <i>v</i>; dimensionless
j	= 1, 2, 3, tree species in plot p
k	= 1, 2, 3, dead trees of species <i>j</i> in plot <i>p</i> in stratum <i>i</i>
p	= 1, 2, 3, sample plots in stratum i
i	= 1, 2, 3, biomass estimation strata within the project boundary
У	= 1, 2, 3, years elapsed since the start of the ZERO2NATURE-PREFOR project activity



Version I.I – Scope 17

6.1.2. Lying dead wood

Lying dead wood is estimated by using line transect method (Harmon and Sexton, 1996). Two transect lines, of total length of at least 100 m, approximately orthogonally bisecting each other at the centre of the plot are established and the diameter of each piece of lying dead wood (with diameter ≥ 10 cm) intersecting a transect line is measured.

Each piece of dead wood is assigned to one of three decay classes and each of the three decay classes are assigned a density reduction factor as explained.

Based on these measurements and categorization into decay classes, carbon stock in lying dead wood of species *j* in plot *p* is calculated as:

$$C_{DWL,j,p,i,y} = \frac{44}{12} \times CF_{TREE} \times D_j * \frac{\pi^2}{8L} \times \sum_{n=1}^N D_{n^2} * \beta_n$$

Equation (6)

Where:

$C_{DWL,j,p,i,y}$	Carbon stock in lying dead wood of species j in sample plot p in stratum i at a given point of time in year y; t EIP
CFTREE	 Carbon fraction of tree biomass; dimensionless
D_j	 Basic wood density of species j; t d.m. m⁻³
L	Sum of the lengths of the transect lines approximately orthogonally bisecting each other at the centre of the plot p; m
D_n	 Diameter of the nth piece of lying dead wood intersecting a transect line; cm
β _n	 Density reduction factor applicable to the nth piece of lying dead wood intersecting a transect line; dimensionless
j	= 1, 2, 3, tree species in plot p
p	= 1, 2, 3, sample plots in stratum <i>i</i>
i	= 1, 2, 3, biomass estimation strata within the project boundary
y	= 1, 2, 3, years elapsed since the start of the ZERO2NATURE-PREFOR project activity



Version I.I – Scope I7

The carbon stock in dead wood in a stratum is then calculated as:

$$C_{DW,i,y} = \frac{A_i}{A_{PLOT,i}} \sum_p \sum_j (C_{DWS_TREE,j,p,i,y} + C_{DWS_STUMP,j,p,i,y} + C_{DWL,j,p,i,y})$$
Equation (7)

141	-	
VV	ner	e:

$C_{DW,i,y}$	Carbon stock in dead wood in stratum <i>i</i> at a given point of tim yeary; t EIP	ne in
A_i	Total area of stratum <i>i</i> ; ha	
$A_{PLOT,i}$	Total area of sample plots in stratum <i>i</i> ; ha	
C _{DWS_TREE} , j, p, i, y	Carbon stock in dead wood in standing dead trees of species sample plot p in stratum i at a given point of time in year y ; t E	sjin IP
C _{DWS_STUMP,j,p,i,y}	Carbon stock in dead wood in dead tree stumps of species j sample plot p in stratum i at a given point of time in year y ; t E	in IP
$C_{DWL,j,p,i,y}$	Carbon stock in lying dead wood of species <i>j</i> in sample plot <i>p</i> stratum <i>i</i> at a given point of time in year <i>y</i> ; t EIP	in
j	1, 2, 3, tree species in plot p	
p	1, 2, 3, sample plots in stratum i	
i	1, 2, 3, biomass estimation strata within the project bound	ary
У	<i>1, 2, 3,</i> years elapsed since the start of the ZERO2NATURE- project activity	PREFOR



Version I.I – Scope I7

Finally, the carbon stock in dead tree biomass within the project boundary at a given point of time in year *y* is calculated by summing up over all the strata, that is:

$$C_{DW,y} = \sum_{i} C_{DW,i,y}$$
Equation (8)

Where:

 Carbon stock in dead wood within the project boundary at a given point of time in yeary; t EIP
 Carbon stock in dead wood in stratum <i>i</i> at a given point of time in yeary; t EIP
= 1, 2, 3, biomass estimation strata within the project boundary
= 1, 2, 3, years elapsed since the start of the ZERO2NATURE-PREFOR project activity

6.2. Conservative default-factor based method for estimation of carbon stock in dead wood

If PPs do not wish to make sampling based measurements for estimation of C stock in dead wood, they may use the default-factor based method described in this section. The default-factor based method is applicable only if dead wood remains *in situ* and is not removed from the project boundary through any type of anthropic activities.

For all strata to which the default-factor based method is applied, the carbon stock in dead wood is estimated as:

$C_{DW,i,y} = C_{TRI}$	$EE,i,y \times$	DF _{DW} Equation (9)
Where:		
$C_{DW,i,y}$	=	Carbon stock in dead wood in stratum <i>i</i> at a given point of time in year <i>y</i> ; t EIP
C _{TREE,i,y}	=	Carbon stock in trees biomass in stratum <i>i</i> at a point of time in year <i>y</i> , as calculated in the tool "Estimation of carbon stocks and change in carbon stocks of trees and shrubs in ZERO2NATURE- PREFOR project activities"; t EIP
DF _{DW}	=	Conservative default factor expressing carbon stock in dead wood as a percentage of carbon stock in tree biomass; per cent
i	=	1, 2, 3, \dots biomass estimation strata within the project boundary
у	=	<i>1</i> , <i>2</i> , <i>3</i> , … years elapsed since the start of the ZERO2NATURE-PREFOR project activity



Version I.I – Scope 17

Value of the conservative default factor expressing carbon stock in dead wood as a percentage of carbon stock in tree biomass (DF_{DW}) is selected according to the guidance provided in the relevant table in Section 8 unless transparent and verifiable information can be provided to justify a different value.

6.3. Change in carbon stock in dead wood

The rate of change of dead wood biomass over a period of time is calculated assuming a linear change. Therefore, the rate of change in carbon stock in dead wood over a period of time is calculated as:

$$dC_{DW,(y_1,y_2)} = \frac{C_{DW,y_2} - C_{DW,y_1}}{T}$$
 Equation (10)

Where:

$dC_{DW,(y_1,y_2)}$	Rate of change in carbon stock in dead wood within the project boundary during the period between a point of time in year y ₁ and a point of time in year y ₂ ; t EIP yr ⁻¹
C_{DW,y_2}	 Carbon stock in dead wood within the project boundary at a point of time in year y₂; t EIP
C _{DW,y1}	 Carbon stock in dead wood within the project boundary at a point of time in year y₁; t EIP
Т	= Time elapsed between two successive estimations $(T=y_2 - y_1)$; yr

Change in carbon stock in dead wood within the project boundary in year $y(y_1 \le y \le y_2)$ is given by:

$$\Delta C_{DW,y} = dC_{DW,(y_1,y_2)} \times 1 \text{ year for } y_1 \le y \le y_2$$
 Equation (11)

Where:

$\Delta C_{DW,y}$	= Change in carbon stock in dead wood within the project boundary
2023	in yeary ; t EIP

dC_{DW},(y₁,y₂) = Rate of change in carbon stock in dead wood within the project boundary during the period between a point of time in yeary₁ and a point of time in yeary₂; t EIP yr⁻¹



Version I.I – Scope I7

7. ESTIMATION OF CARBON STOCK AND CHANGE IN CARBON STOCK IN WASTE

Carbon stock in waste is estimated on the basis of the same strata, and the same sample plots, which are used for the purpose of estimation of living tree biomass. However, PPs applying this tool may use a different stratification for the purpose of estimation of carbon stock in waste if transparent and verifiable information can be given for justification of such a choice.

Two methods are offered for estimation of carbon stock in waste: a measurement-based method and a conservative default-based approach.

7.1. Measurement-based method for estimation of carbon stock in waste

For estimating carbon stock in waste, four waste samples are collected from each sample plot, using a sampling frame which is placed in four randomly selected positions within the plot. The four samples are well mixed into one composite sample and its wet weight is taken. A sub-sample taken from the composite sample is weighed, oven dried, and weighed again to determine its dry weight. The dry-to-wet weight ratio of the sub-sample is calculated and used for estimating the dry weight of the composite waste sample.

Carbon stock in waste biomass in plot *p* is then calculated as:

$C_{W,p,i,y} = \frac{44}{12} \times$	CF _W >	$< 2.5 * \frac{A_{p,i}}{a_{p,i}} \times B_{W_WET,p,i} \times DWR_{W,p,i}$	Equation (12)
	W		
Where:			
$C_{W,p,i,y}$	=	Carbon stock in litter in plot <i>p</i> in stratum <i>i</i> in year	ary;tEIP
CF _W	=	Carbon fraction of dry biomass in waste $\ ;$ dimen default value $\ $ of 0.37 is used)	sionless (IPCC
$B_{W_WET,p,i}$	=	Wet weight of the composite waste sample collective stratum <i>i</i> ; kg	cted from plot <i>p</i> of
$DWR_{W,p,i}$	=	Dry-to-wet weight ratio of the waste sub-sample plot p in stratum i ; dimensionless	collected from
		<u>Note</u> : it is acceptable to determine this ratio for t selected sample plots in a stratum and then app ratio to all plots in that stratum	three randomly ly the average
$A_{p,i}$	=	Area of sample plot p of stratum i; ha	
$a_{p,i}$	=	Area of sampling frame for plot p in stratum i; m	2
		<u>Note</u> : The numerical factor 2.5 appears in this e coversion of units from kg to tonne and from m^2 because of the fact that $B_{W,WBT,p,i}$ is the wet wei collected from an area equal to four times the ar frame	quation because of to <i>ha</i> , as well as ight of waste rea of the sampling
i	=	1, 2, 3, biomass estimation strata within the p	project boundary
р	=	1, 2, 3, sample plots in stratum i	
y	=	1, 2, 3, years elapsed since the start of the ze project activity	RO2NATURE-PREFOR



Version I.I – Scope 17

Carbon stock in waste in stratum *i* is then calculated as:

$$\begin{split} \mathcal{C}_{w,i,y} &= \frac{A_i}{A_{PLOT,i}} \sum_p \mathcal{C}_{w,p,i,y} & \text{Equation (13)} \\ \end{split}$$

$$\begin{split} \text{Where:} & \\ \mathcal{C}_{w,i,y} &= \text{Carbon stock in waste in stratum i at a given point of time in year y; t EIP \\ A_i &= \text{Area of stratum } i; \text{ ha} \\ A_{PLOT,i} &= \text{Area of sample plots in stratum } i; \text{ ha} \\ \mathcal{C}_{w,p,i,y} &= \text{Carbon stock in waste in plot } p \text{ in stratum } i; \text{ t EIP} \\ p &= 1, 2, 3, \dots \text{ sample plots in stratum } i \\ i &= 1, 2, 3, \dots \text{ biomass estimation strata within the project boundary} \\ y &= 1, 2, 3, \dots \text{ years elapsed since the start of the ZERO2NATURE-PREFOR} \end{split}$$

Finally, the carbon stock in waste biomass within the project boundary at a given point of time in year y is calculated by summing up $(C_{W,i,y})$ over all the strata, that is:

$C_{W,y} = \sum_{i} C_{i}$	C _{W,i,y}	Equation (14)
Where:		
C _{W,y}	 Carbon stock in w time in year v; t Elf 	aste within the project boundary at a given point of
C _{W,i,y}	= Carbon stock in wa t EIP	aste in stratum <i>i</i> at a given point of time in year <i>y</i> ;
i	= 1, 2, 3, biomas	s estimation strata within the project boundary
У	= 1, 2, 3, years el project activity	apsed since the start of the ZERO2NATURE-PREFOR

7.2. Conservative default-factor based method for estimation of carbon stock in waste

If PPs do not wish to make sampling based measurements for estimation of C stock in waste, they may use the default-factor based method described in this section. The default-factor based method is applicable only if waste remains *in situ* and is not removed from the project boundary through any type of anthropic activities.



Version I.I – Scope I7

For all strata to which this default method is applied, the carbon stock in waste is estimated as:

DF _W Equation (15)	
 Carbon stock in waste in stratum <i>i</i> at a given point of time in year <i>y</i>; t EIP 	
Carbon stock in trees biomass in stratum <i>i</i> at a point of time in yeary, as calculated in the tool "Estimation of carbon stocks and change in carbon stocks of trees and shrubs in ZER02NATURE- PREFOR project activities"; t EIP	
 Conservative default factor expressing carbon stock in waste as a percentage of carbon stock in tree biomass; percent 	
<i>1, 2, 3,</i> biomass estimation strata within the project boundary	
 1, 2, 3, years elapsed since the start of the ZERO2NATURE-PREFOR project activity 	
	 DF_W Equation (15) Carbon stock in waste in stratum <i>i</i> at a given point of time in year <i>y</i>; t EIP Carbon stock in trees biomass in stratum <i>i</i> at a point of time in yeary, as calculated in the tool "Estimation of carbon stocks and change in carbon stocks of trees and shrubs in ZER02NATURE-PREFOR project activities"; t EIP Conservative default factor expressing carbon stock in waste as a percentage of carbon stock in tree biomass; percent <i>1, 2, 3,</i> years elapsed since the start of the ZER02NATURE-PREFOR project activity

Value of the conservative default factor expressing carbon stock in waste as a percentage of carbon stock in tree biomass (is selected according to the guidance provided in the relevant table in Section 8 unless transparent and verifiable information can be provided to justify a different value.

7.3. Change in carbon stock in waste

The rate of change of waste biomass over a period of time is calculated assuming a linear change. Therefore, the rate of change in carbon stock in waste over a period of time is calculated as:

$dC_{W,(y_1,y_2)} =$	$\frac{C_{W,y_2} - C_{W,y_1}}{T}$ Equa	tion (16)
Where:		
$dC_{W,(y_1,y_2)}$	Rate of change in carbon stock in waste within the project I during the period between a point of time in year y ₁ and a p time in year y ₂ ; t EIP yr ⁻¹	oundary oint of
<i>C</i> _{<i>W</i>,<i>y</i>₂}	 Carbon stock in waste within the project boundary at a poir of time in year ν₂; t EIP 	ıt
C_{W,y_1}	 Carbon stock in waste within the project boundary at a poir of time in year y₁; t EIP 	t
Т	= Time elapsed between two successive estimations (T= y_2 –	<i>v</i> ₁); yr



Version I.I – Scope I7

Change in carbon stock in waste within the project boundary in year $y(y_1 \le y \le y_2)$ is given by:

 $\Delta C_{W,y} = dC_{W,(y_1,y_2)} \times 1 year \text{ for } y_1 \le y \le y_2$

Equation (17)

Where:

 $\Delta C_{W,y} = Change in carbon stock in waste within the project boundary$ in year y; t EIP = Rate of change in carbon stock in waste within the projectboundary during the period between a point of time in year y₁ anda point of time in year y₂; t EIP yr⁻¹

8. DATA AND PARAMETERS USED IN THE TOOL

The following tables describe the data and parameters used in this tool. The guidelines contained in these tables regarding selection of data sources, and procedures to be followed in measurement, where applicable, should be treated as an integral part of this tool.

8.1. Data and parameters not measured

Data / Parameter table 1. Data / Parameter: BEF2. Dimensionless Data unit: Used in equations: Description: Biomass expansion factor for conversion of stem biomass to aboveground biomass for tree species j Values from Table 3A.1.10 of IPCC GPG-LULUCF 2003 are used Source of data: unless transparent and verifiable information can be provided to justify different values Measurement procedures (if any): BEFs in IPCC literature and national inventory are usually applicable Any comment: to closed canopy forest. If applied to individual trees growing in an open field it is recommended that the selected BEF be increased by 30 per cent



K J

ESTIMATIONS OF CARBON STOCKS AND CHANGE IN CARBON STOCKS OF DEAD WOOD AND WASTE IN ZERO2NATURE-PREFOR PROJECT ACTIVITIES

Version I.I – Scope 17

Data / Parameter:	CF _{TREE}
Data unit:	t C t ¹ d.m.
Used in equations:	3, 5, 6
Description:	Carbon fraction of tree biomass
Source of data:	A value of 0.5 shall be used unless transparent and verifiable information can be provided to justify a different value
Measurement procedures (if any):	-
Any comment:	-

Data / Parameter table 3.

Data / Parameter:	CFLI
Data unit:	t C t ⁻¹ d.m.
Used in equations:	12
Description:	Carbon fraction of litter biomass
Source of data:	IPCC default value of 0.37 t C t ⁻¹ d.m. may be used
Measurement procedures (if any):	
Any comment:	- 29

Data / Parameter table 4.

Data / Parameter:	D
Data unit:	t d.m. m ⁻³
Used in equations:	1, 5, 6
Description:	Basic wood density for species j
Source of data:	Values from Table 3A.1.9 of IPCC GPG-LULUCF 2003 are used unless transparent and verifiable information can be provided to justify different values
Measurement procedures (if any):	-
Any comment:	



Version I.I – Scope 17

Data / Parameter table 5.

Data / Parameter:	DF _{DW}				
Data unit:	Per cent				
Used in equations:	9				
Description:	Conservative default factor expressing carbon stock in dead wood as a percentage of carbon stock in tree biomass				
Source of data:	Defaults conserv al. 2006, Glend 2006, Krankina	atively derived fr ay 2008, Kelle and Harmon 19	rom Delaney et al. 1997 r et al. 2004, Eaton an 95, and Clark et al 200	, Smith et nd Lawrence 02:	
	Biome	Elevation	Precipitation	DF _{DW}	
	Tropical	<2000m	<1000 mm yr ⁻¹	2%	
	Tropical	<2000m	1000-1600 mm yr ⁻¹	1%	
	Tropical	<2000m	>1600 mm yr ⁻¹	6%	
	Tropical	>2000m	All	7%	
	Temperate/ boreal	All	All	8%	
Measurement procedures (if any):	2 T.				
Any comment:					

Data / Parameter table 6.

Data / Parameter:	DFLI				
Data unit:	Pe	Per cent			
Used in equations:	15				
Description:	Default factor for the relationship between carbon stock in litter and carbon stock in living trees				
Source of data:	De	efaults conserva	tively derived f	rom sources cited above	ə:
		Biome	Elevation	Precipitation	DFLI
		Tropical	<2000m	<1000 mm yr ⁻¹	4%
		Tropical	<2000m	1000-1600 mm yr ⁻¹	1%
		Tropical	<2000m	>1600 mm yr ⁻¹	1%
		Tropical	>2000m	All	1%
		Temperate/ boreal	All	All	<mark>4</mark> %
Measurement procedures (if any):	-	<u> </u>	+		<u>+</u> ()
Any comment:	-				



Version I.I – Scope 17

Data / Parameter table 7.

Data / Parameter:	R _J	
Data unit:	Dimensionless	
Used in equations:	1, 2, 5	
Description:	Root-shoot ratio for species j	
Source of data:	The value of R_j shall be calculated as: $R = exp[-1.085+0.9256xln(A)]/A$, where A is above-ground biomass (t d.m. ha ⁻¹) [Source: Table 4.A.4 of IPCC GPG-LULUCF 2003] unless transparent and verifiable information can be provided to justify a different value	
Measurement procedures (if any):		
Any comment:	2 ·	

8.2. Data and parameters measured

Data / Parameter table 8.

Data / Parameter:	A _i
Data unit:	ha
Used in equations:	7, 13
Description:	Area of stratum i
Source of data:	Field measurement
Measurement procedures (if any):	Standard operating procedures (SOPs) prescribed under national forest inventory are applied. In the absence of these, SOPs from published handbooks, or from the IPCC GPG LULUCF 2003, may be applied
Monitoring frequency:	Every five years since the year of the initial verification
QA/QC procedures:	Quality control/quality assurance (QA/QC) procedures prescribed under national forest inventory are applied. In the absence of these, QA/QC procedures from published handbooks, or from the IPCC GPG LULUCF 2003, may be applied
Any comment:	50 C



ESTIMATIONS OF CARBON STOCKS AND CHANGE IN CARBON STOCKS OF DEAD WOOD AND WASTE IN ZERO2NATURE-PREFOR PROJECT ACTIVITIES

Version I.I – Scope 17

Data / Parameter table 9.

Data / Parameter:	A _{PLOT,i}	
Data unit:	ha	
Used in equations:	7, 12, 13	
Description:	Total area of sample plots in stratum i	
Source of data:	Field measurement	
Measurement procedures (if any):	Standard operating procedures (SOPs) prescribed under national forest inventory are applied. In the absence of these, SOPs from published handbooks, or from the IPCC GPG LULUCF 2003, may be applied	
Monitoring frequency:	Every five years since the year of the initial verification	
QA/QC procedures:	Quality control/quality assurance (QA/QC) procedures prescribed under national forest inventory are applied. In the absence of these, QA/QC procedures from published handbooks, or from the IPCC GPG LULUCF 2003, may be applied	
Any comment:		

Data / Parameter table 10.

Data / Parameter:	a _{p,i}	
Data unit:	m ²	
Used in equations:	12	
Description:	Area of litter sampling frame used in plot p in stratum i	
Source of data:	Measurement	
Measurement procedures (if any):	Standard operating procedures (SOPs) prescribed under national forest inventory are applied. In the absence of these, SOPs from published handbooks, or from the IPCC GPG LULUCF 2003, may be applied	
Monitoring frequency:	Every five years since the year of the initial verification	
QA/QC procedures:	Quality control/quality assurance (QA/QC) procedures prescribed under national forest inventory are applied. In the absence of these, QA/QC procedures from published handbooks, or from the IPCC GPG LULUCF 2003, may be applied	
Any comment:	Often a litter sampling frame of 0.50 m ² is used	



Version I.I – Scope 17

Data / Parameter table 11.

Data / Parameter:	B _{L1_WET} ,p,i	
Data unit:	Kg	
Used in equations:	12	
Description:	Wet weight of the composite litter sample collected from plot <i>p</i> of stratum <i>i</i> ; kg	
Source of data:	Field measurements in sample plots	
Measurement procedures (if any):	Standard operating procedures (SOPs) prescribed under national forest inventory are applied. In the absence of these, SOPs from published handbooks, or from the IPCC GPG LULUCF 2003, may be applied	
Monitoring frequency:	Every five years since the year of the initial verification	
QA/QC procedures:	Quality control/quality assurance (QA/QC) procedures prescribed under national forest inventory are applied. In the absence of these, QA/QC procedures from published handbooks, or from the IPCC GPG LULUCF 2003, may be applied	
Any comment:		

Data / Parameter table 12.

Data / Parameter:	DBH		
Data unit:	cm or any unit of length as specified		
Used in equations:	1, 2, 4		
Description:	Diameter at breast height of a tree. For the purpose of equations (1) and (2), <i>DBH</i> could be any other diameter or dimensional measurement (e.g. basal diameter, root-collar diameter, basal area, etc.) applicable for the model or data source used		
Source of data:	Field measurements in sample plots		
Measurement procedures (if any):	Standard operating procedures (SOPs) prescribed under national forest inventory are applied. In the absence of these, SOPs from published handbooks, or from the IPCC GPG LULUCF 2003, may be applied		
Monitoring frequency:	Every five years since the year of the initial verification		
QA/QC procedures:	Quality control/quality assurance (QA/QC) procedures prescribed under national forest inventory are applied. In the absence of these, QA/QC procedures from published handbooks, or from the IPCC GPG LULUCF 2003, may be applied		
Any comment:	-		



Version I.I – Scope 17

Data / Parameter table 13.

Data / Parameter:	D _n	
Data unit:	cm	1
Used in equations:	6	1
Description:	Diameter of the n th piece of lying dead wood intersecting a transect line	1
Source of data:	Field measurements along transect lines in sample plots	
Measurement procedures (if any):	Standard operating procedures (SOPs) prescribed under national forest inventory are applied. In absence of these, SOPs from published handbooks, or from the IPCC GPG LULUCF 2003, may be applied	
Monitoring frequency:	Every five years since the year of the initial verification	1
QA/QC procedures:	Quality control/quality assurance (QA/QC) procedures prescribed under national forest inventory are applied. In the absence of these, QA/QC procedures from published handbooks, or from the IPCC GPG LULUCF 2003, may be applied	
Any comment:	-	1

Data / Parameter table 14.

Data / Parameter:	н	
Data unit:	m or any other unit of length as specified	
Used in equations:	1, 2, 4, 5	
Description:	Height of tree	
Source of data:	Field measurements in sample plots	
Measurement procedures (if any):	Standard operating procedures (SOPs) prescribed under national forest inventory are applied. In the absence of these, SOPs from published handbooks, or from the IPCC GPG LULUCF 2003, may be applied	
Monitoring frequency:	Every five years since the year of the initial verification	
QA/QC procedures:	Quality control/quality assurance (QA/QC) procedures prescribed under national forest inventory are applied. In the absence of these, QA/QC procedures from published handbooks, or from the IPCC GPG LULUCF 2003, may be applied	
Any comment:		



Version I.I – Scope 17

Data / Parameter table 15.

Data / Parameter:	Т
Data unit:	Year
Used in equations:	10, 16
Description:	Time period elapsed between two successive estimations of carbon stock
Source of data:	Recorded time
Measurement procedures (if any):	N/A
Monitoring frequency:	-
QA/QC procedures:	
Any comment:	If the two successive estimations of carbon stock are carried out at different points of time in year t_2 and t_1 , (e.g. in the month of April in year t_1 and in the month of September in year t_2), then a fractional value shall be assigned to T

History of the document	Date	Nature of	
Version		revision(s)	
I.I	EC 3, May 4,	Updated	
	2020	-	
1.0	May 8, 2012	Initial	
		adoption.	
Decision Class: Regulatory			
Document Type: Tool			
Business Function: Methodology			